
## CORAWER STORAGE WALL» WIZARD

Side frames with accessories





- Select design M255 (T 27E) or M251 (T 36E)
- Select shelf base area W × D and shelf height H
- Select colour


ΗΛ

For regulatory and safety reasons, drawer shelves must be assembled from at least these elements.



- Select side frame 1
- Floor anchoring, drawer shelves must be anchored.
- For installing drawers with a single or double safety catch, a locking profile is necessary.
- Select the appropriate side frame for using vertical pull-outs 2.
- Optional: frame top covering, intermediate fill-in strip, levelling plates, etc.





- Select stabilising elements: diagonal brace 3 or back panel 4
- When back panels are not used, diagonal braces are absolutely necessary. Please note planning information.
- Optional: side panel covers. Partition walls, shelf side panels 5 to 7

Universal and adjustable shelves with



- Select universal shelves 8 and adjustable shelves 9
- 2 universal shelves should be used for shelf heights up to 2 m. 3 universal shelves should be used for heights of 2.2-3.0 m.
- When using locked and fixed shelves, the universal shelves are dispensed with and serve as top shelves.
- Optional: dividers, folding fronts 10 shelf front cover strips 11

Shelves for drawer inserts




- Select locking and fixed shelves 12
- Fixed and locking shelves incl. lock are used when drawers should be lockable.
- Determine the type of lock KEY, CODE, RFID or AUTO Lock and the height of the lock.





- Select vertical pill-out drawers 16
- Vertical pull-outs in partial and total height and different front widths
- For the use of vertical pull-outs, the appropriate side frames must be selected, 2 incl. lock, top, base and intermediate shelves.
- Strictly follow planning information concerning installation widths of the vertical pull-outs.
- Optional: adjustable shelves, keyholes, storage shelves and locking brackets

8. Protruding parts



- Select protruding parts: hinged doors, sliding doors, roller shutters 17 to 19
- Strictly follow planning information concerning protruding part variants.
- Roller shutters always include a top shelf
- Hinged door and sliding door cover can be used both left as well as right in conjunction with side panel covers.




- Select safety ladders 20
- Up to 3 m bearing height for servicing
- Ladder can be folded and is accessible on the left as well as the right

and fixed shelves, i.e. the sum total of the drawer front heights (C) must correspond to the clear height (B)

labelling system»



- Select drawer 13
- Determine front height, load capacity and drawer safety catch
- In the case of locked drawers, the clear height of the lock is decisive for locking
- For appropriate partition material, see section «Partition materials &



- Select pull-out shelves 14 and heavy-duty pull-out shelves 15
- Multiplex supports and slat inserts for heavy-duty pull-out shelves
- Optional: pull-out shelves with eyelets